



# Biglift 2.65 F 550 MB

Electro-hydraulic twin-ram lift, 6.5 t with platforms

The product meets the requirements for workshop equipment for MB service workshops and is recommended by Mercedes Benz with approval no. H23 13 10 7A.

Biglift 2.65 F 550 – H23 13 10 7A



Order no.	Item no.	#	Part of the approval according to order no. 20010107-1/-2:
20010107-1	21507	1	Superstructure BL 2.65 F 550
	21100	1	Drive-on ramp, on floor, 1100 mm, 10°, 1 set = 2 pcs.
	21084	1	Roll-off safety device, h = 100 mm, 1 set = 2 pcs.
	12465	1	M, Mercedes-approval and painting - type F - grey RAL 7015
	12407	1	Extra charge zinc coated and painted platforms
	21080	1	Power distribution for one platform
	21096	1	Pneumatic installation for 1 side of the platform
	11103	1	Document holder AUTOPSTENHOJ
	11104	1	Magnetic tool tray set, 1 set = 2 pcs.
	21093	1	Jacking beam A air hydr. 4 t, incl. innovative air supply, suspension BL 2.65 F
	12468	1	M, Mercedes-approval and painting - scissor jack 4.0 t, RAL 7015
20010107-2	12925	1	Lifting pad adapter for jacking beam
	11027	2	Pad Ø120/95/135
	10291	1	Hydraulic unit BL 2.65 - 1550, cylinder Ø213, stroke 1860
	12036	1	Ecological hydraulic fluid 17 ltr.
	11109	1	16A circuit breaker in the control box
			<b>Not part of the approval (options)</b>
	11063	1	Set of cables 10 m
	12173	1	Cassette BL PD 1550

The Biglift 2.65 F 550 repair platform is optimally suited for **quick and easy vehicle lifting**.  
 The premium version is constructed of very strong and rigid **solid steel** that offers a **high degree of stability**.  
 They are zinc coated and painted. Looks great and works great!  
 Two **strong 213 mm diameter cylinders** are also designed for long-lasting functionality and further round off the high-quality level, which ensures **low maintenance requirements**.  
 Even in the event of a power blackout, the lift can still be lowered without any problems thanks to the pneumatic emergency lowering system.  
 The Biglift 2.65 F 550 is perfectly completed by a **control system that is both visually and technically convincing**.

**Standard color:**  
RAL 7015 grey

**Options:**  
LED lighting set  
Scissor jacks

**Installation:**  
Superstructure on floor  
Superstructure recessed

**Steel cassette:**  
Standard: Primed  
Optional: Hot-dip galvanised or plastic-coated

