BMW & MINI

Maestro 32 F BMW

Electro-mechanical 2-post lift, 3.2 t capacity



Order no.	ltem no.	#	Part of the approval according to order no. 20011118:
20011118	089185	1	Maestro 32 F - DT/DT, 400/3/50 - 4050/4350mm - Ø40 - RAL 9010/7016
	777473	1	Set of 14 expansion anchor bolts - HST3 M12x115 40/20
	776477	1	Portal set for Maestro 2.30/2.32/30/32, 4050mm

The 2-post lifts of the Maestro 32/35 series impress with their premium construction. They come with **stable bent columns**. Smooth running is ensured by the **sliding bearing carriage**. The **cold-rolled spindle** guarantees an **particularly long service life**. The columns are asymmetrically positioned, i.e. vehicles can be positioned far to the rear, which ensures an **optimal door opening angle**.

Of course, the Maestro 32 also has door stop protection to prevent damage when entry and exit. The **swivel arms are extremely flat** and thus ensure a **low minimum height**. The **internal arm locking system** with strong 360° interlocking protects against moisture and dirt.


Standard colour:

Arms: RAL 3020 Posts: RAL 7016

Options:

Available with different portal heights LED lighting set Energy set with compressed air and socket-outlet Extra control unit for second column Large program of extra pads, depending on type of vehicle

Versions: Available for different voltages F = flex pad



UPLIFTING COMPANY

AUTOP STENHOJ

