



Masterlift 2.35 NxT Pv 160-220 xy MB

Electro-hydraulic twin-ram lift, 3.5 t with repair platforms

The product meets the requirements for workshop equipment for MB service workshops and is recommended by Mercedes Benz with approval no. H13 01 01 1A.

Masterlift 2.35 NxT Pv – H13 01 01 1A



Order no.	Item no.	#	Part of the approval according to order no. 20010100:
20010100	14107	1	Superstructure ML 2.35 Pv 160-220 xy
	16070	1	Hydraulic unit ML 2.35 NxT, Ø140, PD 1350, stroke 1915mm incl. Side covers for cassette PD 1550
	12033	1	Ecological hydraulic fluid 10 ltr.
	12462	1	Mercedes approval and painting type: "Pv", RAL 7015 grey
	11102	1	Rubber blocks 40mm, 1 set = 4 pcs.
	11103	1	Document holder "AUTOPSTENHOJ"
	11104	1	Magnetic tool tray set, 1 set = 2 pcs.
	11063	1	Set of cables 10 m
	14096	1	Cassette ML PD 1550

The Masterlift 2.35 NxT Pv repair platform is optimally suited for **quick and easy vehicle lifting**.

The premium version is constructed of very strong and rigid **solid steel** that offers a **high degree of stability**. They are zink coated and painted. Looks great and works great! Alternatively, we also offer an economical version made from a welded profile that is hot dip galvanized.

Various lengths of repair platforms, which come with **xy-function in the premium version as standard**, make the Masterlift 2.35 NxT the perfect helper in your workshop. Optionally, longitudinally adjustable supports can be supplied instead of the xy function.

The handy, **non-slip and form-fitting rubber pads** ensure that the vehicle is lifted with pinpoint accuracy.

The **strong 140 mm diameter cylinders** are also designed for long-lasting functionality and further round off the high-quality level, which ensures **low maintenance requirements**.

Even in the event of a power blackout, the lift can still be lowered without any problems thanks to the pneumatic emergency lowering system.

The Masterlift 2.35 NxT Saa is perfectly completed by a **control system that is both visually and technically convincing**.

Standard color:

Pv Premium: zink coated and painted - RAL 9006

Pv Standard: hot-dip galvanized, without painting

Options:

Longitudinally adjustable supports

Rubber blocks in different heights

Frame:

Standard: completely hot-dip galvanized

Sub-casing:

Standard: painted

Optional: hot-dip galvanized or plastic-coated

Versions:

Synchronisation and safety via synchronisation bar and toothed rack

Self-supporting installation, without load on the bottom of the sub-casing

Installation variants:

On-floor installation

Recessed installation (only for Pv Premium)

Ceiling installation

