BMW & MINI

Masterlift 2.35 NxT TR Saa BMW

Electro-hydraulic twin-ram lift, 3.5 t with swivel arms





Order no.	Item no.	#	Part of the approval according to order no. 20011113-1/-2:
20011113-1	21547	1	Swivel arm superstructure 2.35 NxT Rack and Pinion Saa 260 Universal
20011113-2	14130	1	Lifting unit ML 2.35 NxT TR KA 2600, 2000mm stroke with cardan shaft
	11063	1	Set of cables 10m (Std. EL, ML, PL, BL)
	12033	1	Ecological hydraulic fluid 10 ltr.

The double telescopic swivel arms convince with a **very low minimum height**, which even makes it possible to lift low-profile sports cars without any problems.

Tyres and rims are protected in the best possible way by the rounded design of the superstructure's chassis. The **internal arm locking system** installed as standard reliably protects against external influences.

The **strong 140 mm diameter cylinders** are also designed for long-lasting functionality and further round off the high-quality level, which ensures **low maintenance requirements**.

Even in the event of a power blackout, the lift can still be lowered without any problems thanks to the pneumatic emergency lowering system.

The Masterlift 2.35 NxT TR Saa is perfectly completed by a **control system that is both visually and technically convincing**.

Standard color:

Base plate: RAL 7016 Arms: RAL 3020 - optionally with KTL coating

Options:

Wide range of extra pads, depending on vehicle type Special colours on request

Standard:

Basically self-supporting design

Installation variants:

On-floor installation Recessed installation Ceiling installation

Frame:

Standard: completely hot-dip galvanized Incl. tube connection frame

