

Masterlift 2.35 Combi Check-in PD 1550 MB

Electro-hydraulic twin-ram lift, 3.5 t with platforms and wheel-free device



he product meets the requirements for workshop equipment or MB service workshops and is recommended by Mercedes enz with approval no. H12 01 04 1L

Masterlift 2.35 Combi Check-in– H12 01 04 1L

	Order no.	ltem no.	#	Part of the approval according to order no. 20010103-1/-2:
MB H12 01 04 1L Order no. 20010103-1 20010103-2	20010103-1	21500	1	Superstructure 2.35 F 440 Combi Check-in, on floor
		12466	1	Mercedes approval and painting, type Fn/Combi, grey RAL 7015
		12407	1	Extra charge zinc coated and painted platforms
		21080	1	Power distribution for one platform
		21097	1	Pneumatic installation for 1 side of the platform
		11102	1	Rubber blocks 40 mm, 1 set = 4 pcs.
		11103	1	Document holder AUTOPSTENHOJ
		11104	1	Magnetic tool tray set, 1 set = 2 pcs.
	20010103-2	21504	1	Repair platform superstructure 2.35 Pv 160-220 xy
		10290	1	Hydraulic unit ML 2.35 Combi Check in PD 1550, stroke 1900 mm
		12036	1	Ecological hydraulic fluid 17 ltr.
		11109	1	16A circuit breaker in the control box
				Not part of the approval (options)
		11071	1	Set of cables 10 m
		12117	1	Cassette PD 1550. ML Combi Check in

The Masterlift 2.35 Combi Check-in PD is optimally suited for quick and easy vehicle lifting.

The platform is constructed of very strong and rigid **solid steel** that offers a **high degree of stability**. They are zinc coated and painted. Looks great and works great! Various lengths of repair platforms, which come with **xy-function in the premium version as standard**, make the Masterlift 2.35 NxT the perfect helper in your workshop. Four **strong 123 mm diameter cylinders** are also designed for long-lasting functionality and further round off the high-quality level, which ensures **low maintenance requirements**.

Even in the event of a power blackout, the lift can still be lowered without any problems thanks to the pneumatic emergency lowering system.

The Masterlift Combi Check-in KA 1550 is perfectly completed by a **control system that is both visually and technically convincing**.

Standard color:

Platforms: RAL 7015 and aluminium coated and integrated LED lighting Pv Premium: zinc coated and painted RAL 7015

Options:

XY-pads Sets of rubber blocks, 40, 60, 80 and 100 mm

Installation:

Superstructure on floor Superstructure recessed

Steel cassette:

Standard: Primed Optional: Hot-dip galvanised or plastic-coated

