



**BMW 08 502673**  
Order no. 20011112-1 & 20011112-2

Order no.	Item no.	#	Part of the approval according to order no. 20011112-1/-2:
20011112-1	21214	1	Swivel arm superstructure 2.35 Saa 260 Universal
20011112-2	14051	1	Hydraulic unit ML 2.35 NxT, Ø 140mm, PD 2600, stroke 1915mm
	11063	1	Set of cables 10m (Std. EL, ML, PL, BL)
	12033	1	Ecological hydraulic fluid 10 ltr.

The double telescopic swivel arms convince with a **very low minimum height**, which even makes it possible to lift low-profile sports cars without any problems. Tyres and rims are protected in the best possible way by the rounded design of the superstructure's chassis. The **internal arm locking system** installed as standard reliably protects against external influences.

The **strong 140 mm diameter cylinders** are also designed for long-lasting functionality and further round off the high-quality level, which ensures **low maintenance requirements**. Even in the event of a power blackout, the lift can still be lowered without any problems thanks to the pneumatic emergency lowering system. The Masterlift 2.35 NxT Saa is perfectly completed by a **control system that is both visually and technically convincing**.

#### Standard color:

Base plate: RAL 7016

Arms: RAL 3020 - optionally with KTL coating

#### Options:

Wide range of extra pads, depending on vehicle type

Active cassette ventilation

Moisture monitoring in the steel cassette

Special colours on request

#### Versions:

Self-supporting design, without load on the bottom of the cassette

Floor-standing design

#### Installation variants:

On-floor installation

Recessed installation

Ceiling installation

#### Frame:

Standard: completely hot-dip galvanized

#### Sub-casing:

Standard: painted

Optional: hot-dip galvanized or plastic coated

