

Sharklift 4.55 F 480 BMW

Electro-hydraulic 4-ram lift, 6.5 t, with platforms



BMW 08 501885
 Order no. 20011103-1 & 20011103-2

Order no.	Item no.	#	Part of the approval according to order no. 20011103-1/-2:
20011103-1	21538	1	Platform superstructure 4.55 F 480 PD 1550/3000 with cross beams
	12455	1	AUTOPSTENHOJ painting - grey RAL 7016 - red RAL 3020
	20547	1	Sliding plates autop-Premium (1 set = 2 pieces)
	21536	1	Automatically rising stoppers SHL 4.55 (1 Set = 2 pcs) for recessed installation with cross beam
	12942	1	LED Illumination, 3 pieces per platform
	12461	1	BMW-approval and painting - grey RAL 7016
20011103-2	10299	1	Hydraulic unit SHL 4.55, Zyl. Ø 140, stroke 1875mm
	11073	1	Electrical connection cables
	12040	1	Ecological hydraulic fluid, 20 ltr.

The Sharklift 4.65 F 550 is optimally suited for **quick and easy wheel alignment**. The platform is constructed of very strong and rigid **solid steel** that offers a **high degree of stability**. They are zinc coated and painted. Looks great and works great!
 The Sharklift 4.65 F 550 also impresses with its enormous precision! Four **strong 213 mm diameter cylinders and four mechanical safety ratchets** are also designed for long-lasting functionality and further round off the high-quality level, which ensures **low maintenance requirements**.
 The Sharklift 4.65 F 550 is perfectly completed by a **control system that is both visually and technically convincing**.

Standard color:
 RAL 7016 / RAL 3020

Options:
 LED-lighting set
 Scissor jack

Installation:
 Superstructure on floor
 Recessed installation with or without flush-floor device

Steel cassette:
 Standard: primed
 Optional: hot-dip galvanized or plastic coated

