

Sharklift 4.65 F 550 MB

Electro-hydraulic 4-ram lift, 6.5 t, with platforms







Order no.	ltem no.	#	Part of the approval according to order no. 20010108-1/-2:
20010108-1	21072	1	Superstructure SHL 4.65 F 550 - KA 1550/3000
	21095	1	Long drive-on ramps 1400 mm, 8° (1 Set = 2 pcs.) 4.65
	21116	1	Roll-off safety device QL 4.55 / 4.65, 1 Set = 2 pcs.
	12465	1	M, Mercedes-approval and painting - F - grey RAL 7015
	12420	1	Extra charge for spray-galvanized platforms QL 4.65
	21080	1	Power distribution for one platform
	21081	1	Pneumatic installation QL 4.65 for 1 side of the platform
	11103	1	Document holder AUTOPSTENHOJ
	11104	1	Magnetic tool tray set, 1 set = 2 pcs.
	20549	2	Sliding plates MB version (1 set = 2 pcs.)
	21075	1	Jacking beam A air hydr. 4 t, incl. innovative air supply, suspension SHL 4.65
	12468	1	M, Mercedes-approval and painting - scissor jack 4.0 t, RAL 7015
	12925	1	Lifting pad adapter for jacking beam
	11027	2	Pad Ø120/95/135
	21076	1	MKS console cpl. rotatable, MB-version
20010108-2	10293	1	Hydraulic unit SHL 4.65 Cyl. Ø 213, stroke 1865 mm, PD 1550/3000
	12042	1	Ecological hydraulic fluid, 24 ltr.
			Not part of the approval (options)
	11073	1	Set of cables QL 4.65
	12310	1	Set of cassettes SHL PD 1550/3000

The Sharklift 4.65 F 550 repair platform is optimally suited for **quick and easy wheel alignment**. The platform is constructed of very strong and rigid **solid steel** that offers a **high degree of stability**. They are zinc coated and painted. Looks great and works great!

The Sharklift 4.65 F 550 also impresses with its enormous precision! Four strong 213 mm diameter cylinders and four mechanical safety ratchets are also designed for long-lasting functionality and further round off the high-quality level, which ensures low maintenance requirements.

The Sharklift 4.65 F 550 is perfectly completed by a control system that is both visually and technically convincing.

Standard color:

RAL 7015 grey

Options:

Large program of extra pads, depending on type of vehicle Special colours available on request

Installation:

Superstructure on floor Superstructure in floor with covers (Saaa 230) Ceiling installation (Saaa 230)

Steel cassette:

Hot galvanized Coated Self-carrying (Saaa 230)

2

2

