

Sololift 1.35 Pv VW

Electro-hydraulic centre-ram lift 3.5 t with flat lifting support





Order no.	Item.	#	Part of the approval according to order no. 20012118:
20012118	21518	1	Superstructure 1.35 Pv 160-220 Ø213
	12458	1	VW specification VAS 781 007
	10306	1	Hydraulic unit SL 1.35 with integrated pump unit, stroke 1910 mm , cylinder Ø 213mm
	11063	1	Set of cables 10 m
	11060	1	Surcharge for 1 set xy-heads
	12034	1	Ecological hydraulic fluid 14 ltr.

The Sololift 1.35 Pv is ideal for quick and convenient vehicle pick-up.

The premium flat lifting support made of very strong and rigid solid material, which ensures a high degree of stability. It is zinc sprayed and painted. This not only looks good, it also works well!

The handy, non-slip and form-fitting rubber pads ensure that the vehicle is lifted precisely.

The strong cylinder with a diameter of 213 mm is also designed for long-lasting functionality and further rounds off the high-quality level, which ensures low maintenance requirements.

Even in the event of a power blackout, the lift can still be lowered without difficulty thanks to the pneumatic emergency lowering device.

Sololift 1.35 Pv is perfectly completed by a control system that is both visually and technically convincing.

Standard colour:

RAL 7012

Optionen:

Rubber pads in different heights

Installation variants:

Superstructure on floor with hydraulic pump unit in floor Not included in the scope of approval, please order separately:

Steel cassette:

Self supporting Standard: painted

Optional: hot-dip galvanized or plastic-coated

